

WAAS CH 45732 W35A	APP CRS 346°	Rwy Idg TDZE Apt Elev	4010 1522 1523
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 35

LANGLADE COUNTY (AIG)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Wausau Downtown altimeter setting. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Wausau Downtown altimeter setting: increase all DA 105 feet and visibility LPV all Cats ¼ mile and LNAV/VNAV all Cats ¾ mile; increase all MDA 120 feet and visibility LNAV Cat C/D and Circling Cat C ½ mile and Circling Cat D ¼ mile.

MISSED APPROACH:
Climb to 3400 direct
OZOX Y and hold.

AWOS-3 119.075	MINNEAPOLIS CENTER 124.4 317.7	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 1523	TDZE 1522
------------------	------------------



3400	OZOX Y	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 36).			
* LNAV only.		4 NM Holding Pattern			
* 1.3 NM to RWY 35		3300			
1.3		4.2 NM			
7 NM		3300			
3400		3300			
166°		346°			
GP 3.00°		TCH 40			
CATEGORY	A	B	C	D	
LPV DA	1772-1		250 (300-1)		
LNAV/VNAV DA	2019-1¾		497 (500-1¾)		
LNAV MDA	1960-1	438 (500-1)	1960-1¼	438 (500-1¼)	
CIRCLING	2120-1	597 (600-1)	2120-1½ 597 (600-1½)	2120-2 597 (600-2)	