

WAAS
CH 81923
W18A

APP CRS
174°

Rwy Idg 5001
TDZE 1177
Apt Elev 1193

RNAV (GPS) RWY 18

SUNDANCE (HSD)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Wiley Post altimeter setting. DME/DME RNP-0.3 NA. Circling Rwy 36 NA at night.


MISSED APPROACH:
Climb to 3200 direct NUFAD and hold.

AWOS-3
120.975

OKE CITY APP CON
124.6 266.8

CLNC DEL
123.7

UNICOM
122.7 (CTAF) 0



MISSED APCH FIX
NUFAD

4 NM

2283

WAROP 1.7 NM to RW18

ILWIM 2800

RW18 1279 ±

1441

1208

1538

2758

ELEV 1193

TDZE 1177

174° to RW18

81

0.8g UP

5001 X 100

36

MIRL Rwy 18-36 0

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).

YAVOR

3600

354°

174°

174°

ILWIM 2800

WAROP 1.7 NM to RW18

*1.1 NM to RW18

*1720

7.1 NM

3.4 NM

0.6

1.1

GP 3.00° TCH 40

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	1427-1	250 (300-1)		NA
LNAV/VNAV DA	1473-1½	296 (300-1½)		NA
LNAV MDA	1540-1	363 (400-1)	1540-1½ 363 (400-1½)	NA
CIRCLING	1740-1 547 (600-1)	1840-1 647 (700-1)	1840-1¾ 647 (700-1¾)	NA