



APP CRS	Rwy Idg	4504
332°	TDZE	269
	Apt Elev	269

RNAV (GPS) RWY 33

GIDEON MEML (M85)

▼ ▲ NA	DME/DME RNP-0.3 NA. Procedure NA at night. Helicopter visibility reduction below 1 SM NA. Obtain Arkansas Intl altimeter setting on CTAF (122.7), when not received, use Poplar Bluff altimeter setting and increase all MDA 20 feet and Circling Cat C visibility ¼ mile.	MISSED APPROACH: Climb to 2400 direct UMEMY and hold.
--	--	---

BYH CTAF 122.7	MEMPHIS CENTER 133.65 292.15	CTAF 122.9
-------------------	---------------------------------	---------------



2400 ↑		UMEMY ✦		ZOXUM		4 NM Holding Pattern	
RW33 2 NM		ZESBO 2 NM to RW33 3 NM		WEPKI 7 NM		1900 332°	
		3.00° TCH 40		152° 332°		2400	
CATEGORY	A		B		C		D
LNNAV MDA	740-1 471 (500-1)		740-1 $\frac{3}{8}$ 471 (500-1 $\frac{3}{8}$)		NA		
CIRCLING	860-1 591 (600-1)		900-1 $\frac{3}{4}$ 631 (700-1 $\frac{3}{4}$)		NA		